

## Max. kabellengte (mtr.) voor bronpompen

### 1 FASE 230V 50Hz

Motor type		Kabel type mm <sup>2</sup>						
kW	Pk	4x1	4x1,5	4x2,5	4x4	4x6	4x10	4x16
0,25	0,33	70	105	170				
0,37	0,50	60	90	140				
0,55	0,75	45	70	110	180			
0,75	1,0	35	50	85	140	210		
1,1	1,5	25	35	60	95	145	240	
1,5	2,0		30	45	75	115	190	350
2,2	3,0			30	50	75	125	200

### 3 FASE 230V 50Hz

Motor type		Kabel type mm <sup>2</sup>										
kW	Pk	4x1	4x1,5	4x2,5	4x4	4x6	4x10	4x16	4x25	4x35	4x50	4x70
0,37	0,50	100	152	255								
0,55	0,75	83	126	210	338							
0,75	1,0	65	99	165	265	405						
1,1	1,5	48	72	120	192	292	485					
1,5	2,0		53	88	142	215	360					
2,2	3,0			60	97	147	245	392				
3,0	4,0			47	73	110	183	295	510			
4,0	5,5				55	83	138	220	380			
5,5	7,5					60	100	160	275	385		
7,5	10,0					45	73	114	195	275	395	
9,2	12,5						64	100	157	220	315	
11,0	15,0						54	87	135	190	270	378
13,0	17,5							75	117	164	236	330
15,0	20,0							65	102	144	205	287
18,5	25,0								82	114	162	225
22,0	30,0								69	95	137	190
30,0	40,0									70	102	142

### 3 FASE 400V 50Hz

Motor type		Kabel type mm <sup>2</sup>										
kW	Pk	4x1	4x1,5	4x2,5	4x4	4x6	4x10	4x16	4x25	4x35	4x50	4x70
0,37	0,50	300										
0,55	0,75	250	380									
0,75	1,0	195	295									
1,1	1,5	145	215	360								
1,5	2,0	105	160	265	425							
2,2	3,0	70	110	180	290	440						
3,0	4,0	55	85	140	220	330						
4,0	5,5	40	60	105	165	250	415					
5,5	7,5		45	75	120	180	300	480				
7,5	10,0		35	55	95	135	220	340	585			
9,2	12,5			47	75	115	190	300	470			
11,0	15,0			40	65	95	160	260	405			
13,0	17,5				60	85	140	225	350	490		
15,0	20,0				50	75	125	195	305	430		
18,5	25,0					58	100	155	245	340	485	
22,0	30,0					49	85	130	205	285	410	570
30,0	40,0					36	63	96	152	210	305	425

3% spanningsverlies - max. omgevingstemperatuur +30°C